

















Product quality			
<b>Format</b>		1209 x 219 x 4,3 mm	598 x 294 x 4,3 mm
<b>Packaging</b>	<b>Pack:</b>	9 elements / 2.383 m <sup>2</sup> / 20.2 kg	11 elements / 1.934 m <sup>2</sup> / 15 kg
	<b>Pallet:</b>	42 packs / 100.08 m <sup>2</sup> / 863.4 kg	48 packs / 92.83 m <sup>2</sup> / 735 kg
Tolerances EN ISO 10582			
<b>Weight per unit area</b>		≥ 8700 g/m <sup>2</sup>	
<b>Squareness of the elements (≤ 0.25 mm)</b>		≤ 0,10 mm/m	
<b>Determination of linearity (≤ 0.35 mm/m)</b>		≤ 0,20 mm/m	
<b>Dimensional stability after exposure to heat (≤ 0,15 %)</b>		≤ 0,15 %	
<b>Curling after exposure to heat (≤ 1mm)</b>		≤ 1mm	
Guarantee (According Parador guarantee conditions)		Notes	
Domestic area	Commercial area	- suitable for all-over adhesion - cleaning and maintenance see instructions - technical changes reserved	
10 years	-		
   		Quality Production Controlled Functionality www.tuv.com ID 000005715	

Classification			
		Test method	Rating
	<b>Utility class 23</b> domestic areas with intensive use	EN ISO 10582	Living room, hall, kitchen, home office
	<b>Utility class 31</b> commercial areas with low use	EN ISO 10582	Hotels, small offices
	Wear layer	EN ISO 24340	0,3 mm
	Surface Coating		PUR
	Reaction to fire	EN 13501-1	C <sub>s</sub> s1
	Slip resistance	EN 13893 EN 14041	μ ≥ 0,35 DS
	Staining resistance	ISO 26987	Index 0, Not affected
	Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
	<b>Thermal resistance</b> Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier.	EN 12664	0,025 m <sup>2</sup> *K/W
	Moving a furniture leg	EN 424	No visible changes
	Indentation-residual	EN ISO 24343-1	≤ 0,10 mm
	Acoustical - Impact noise reduction	ISO 717-2	17 dB (on Akustik-Protect 100)
	Locking strength	EN ISO 10582	≥ 1,5 kN/m
	Antimicrobial activity	ISO 22196	Antibacterial
	Slip resistance on an inclined plane	DIN 51130	Brushed, mineral, stone, vivid texture: R 9 / Rough-sawn texture : R 10
	Disposal	EAK-Code-number	20 01 39

Changed:	QMB Parador	File:	20180901_PA_TDS_Vinyl_Basic-4.3_EN
Date:	01.06.2012	Latest update at:	<a href="http://www.parador.eu/service/catalogues-downloads/technical-data-sheets">www.parador.eu/service/catalogues-downloads/technical-data-sheets</a>
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.09.2018