



















Product quality		
Format		1209 x 219 x 5 mm
Packaging	Pack:	8 elements / 2.118 m ² / 19.63 kg
	Pallet:	42 packs / 88.96 m ² / 839.46 kg
Tolerances EN ISO 10582		
Weight per unit area		≥ 9700 g/m ²
Squareness of the elements (≤ 0.25 mm)		≤ 0,10 mm/m
Determination of linearity (≤ 0.35 mm/m)		≤ 0,20 mm/m
Dimensional stability after exposure to heat (≤ 0,15 %)		≤ 0,15 %
Curling after exposure to heat (≤ 1mm)		≤ 1mm
Guarantee (According Parador guarantee conditions)		Notes
Domestic area	Commercial area	- suitable for all-over adhesion
Lifetime	10 Years	- cleaning and maintenance see instructions - technical changes reserved
   		

Classification			
		Test method	Rating
	Utility class 23 domestic areas with intensive use	EN ISO 10582	Living room, hall, kitchen, home office
	Utility class 33 commercial areas with intensive use	EN ISO 10582	Classrooms, open-plan offices, shops
	Utility class 42* industrial areas with medium use	EN ISO 10582	Storage rooms or moderately used Production areas
	Wear layer	EN ISO 24340	0,55 mm
	Surface Coating		PUR
	Reaction to fire	EN 13501-1	B _{fl} s1
	Slip resistance	EN 13893 EN 14041	μ ≥ 0,50 DS
	Staining resistance	ISO 26987	Index 0, Not affected
	Light fastness	EN ISO 105 – B02	Blue wool scale: Stage ≥ 6
	Resistance to roller castor chairs	ISO 4918	Type W, no visible changes
	Thermal resistance Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier.	EN 12664	0,029 m ² *K/W
	Moving a furniture leg	EN 424	No visible changes
	Indentation-residual	EN ISO 24343-1	≤ 0,05 mm
	Acoustical - Impact noise reduction	ISO 717-2	13 dB (on Akustik-Protect 100)
	Locking strength	EN ISO 10582	≥ 1,5 kN/m
	Antimicrobial activity	ISO 22196	Antibacterial
	Slip resistance on an inclined plane	DIN 51130	Antique, brushed, rustic texture: R 9
	Disposal	EAK-Code-number	20 01 39

* only in case of all-over-adhesion

Changed:	QMB Parador	File:	20180901_PA_TDS_Vinyl_Classic-2050_EN
Date:	01.06.2012	Latest update at:	www.parador.eu/service/catalogues-downloads/technical-data-sheets
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.09.2018